



# grandMA3 onPC 8Port Node 4k

Art.-No. 4010514



The grandMA3 onPC 8Port Node 4K enables 4 096 parameters with the grandMA3 onPC software and has 8 DMX outputs on the rear side. Packed in a 19" 1RU housing, it is suitable for touring and fixed installations and is the most powerful Ethernet to DMX converter for the grandMA3 onPC solutions.

MA Lighting offers the perfect solutions for getting started with. Simply download the grandMA3 onPC software and connect to any of the grandMA3 onPC products to unlock parameters.

The amount of DMX outputs varies with each grandMA3 onPC product but all of them unlock parameters for the full grandMA3 software functionality. There is no compromise in feature set and the range of products allow you to make the right choice for your budget or individual needs.

There are four choices for onPC solutions: the grandMA3 onPC command wing XT, featuring a built-in MA mother board, the grandMA3 onPC command wing, which offers the ultimate grandMA3 mobile solution, the grandMA3 onPC fader wing as fader extension, and the grandMA3 onPC xPort Nodes, which offer the most cost-effective DMX output solution for software-only show control.

Every grandMA3 onPC xPort Node is capable of handling MA-Net3, MA-Net2, sACN and Art-Net data and is fully RDM compliant. A 3.9" color display on the front face allows for simple configuration and provides a quick overview of the status of each Node.

All grandMA3 onPC xPort Nodes are equipped with a powerful processor and a 1 000 Mbit/s Ethernet connection to ensure the most reliable and stable Ethernet to DMX and vice versa conversion.

The grandMA3 onPC xPort Nodes are high quality solutions that can handle busy Ethernet connections without ditching DMX or RDM messages.



Scope of delivery

1x powerCON TRUE1 connector (NAC3FX-W)

Technical Specifications

<b>Parameters</b>	4 096 (HTP/LTP)
<b>Parameters Mode2</b>	2 048 (HTP/LTP)
<b>Operating voltage/ Supply voltage</b>	100-240V, 50/60Hz
<b>Power</b>	max. 15VA
<b>Operating Temperature</b>	0 °C up to 40 °C / 32 °F up to 104 °F
<b>Dimensions</b>	482 x 189 x 43 mm / 19 x 8 x 2 in (width x depth x height)
<b>Net weight</b>	2 kg / 5 lbs
<b>Connectors</b>	1 x powerCON TRUE1 1 x etherCON/RJ45 8 x DMX512-A Out (5pin XLR female) 1 x USB 2.0 (type A)

Article

Art.-No.	Article
4010514	grandMA3 onPC 8Port Node 4k

Accessories

Art.-No.	Article
130284	MA 2Port / 4Port / 8Port Node rigging plate

More product pictures

