



OVERVIEW

ORDERING INFORMATION

DMX Widgets allow you to easily expand your console's DMX output. Simply attach a USB DMX Widget and - just like that - you have more DMX outputs. Each standard DMX Widget adds one universe. The DMX Super Widget adds four ports and universes, and the DMX Super Duper Widget adds eight.

The MIDI/LTC Widget provides a single Linear Timecode input and MIDI in/out/thru for any Hog 4 OS consoles and any Hog 4 PC. When used in conjunction with Hog 4, Full Boar 4, or Road Hog 4, the LTC Widget provides a powerful level of timecode functionality.

PRODUCT FEATURES (DMX WIDGETS)

- USB connection to any Hog 4 console as well as Hog 4 PC
- Single DMX-512 output per 5-pin XLR connector
- Multiple USB DMX Widgets can be connected via USB Hub
- Kensington security slot

PRODUCT FEATURES (MIDI/LTC WIDGET)

- One USB input connector providing power
- One Linear Timecode (LTC/SMPTE) input on 3 pin XLR connector
- MIDI in/out/thru supporting MIDI messages, MIDI Show Control, and MIDI Time Code
- Multiple USB MIDI/LTC Widgets can be connected via USB Hub
- Kensington security slot

Widgets

MODEL	DESCRIPTION
74040011	USB DMX Widget
74040008	USB DMX Super Widget
62040005	USB DMX Super Duper Widget (DMX Processor 8000 expander)
74040009	USB MIDI/LTC Widget



PRODUCT SPECIFICATIONS

DMX WIDGET SPECIFICATIONS

- USB connection to any Hog 4 console as well as Hog 4 PC
- Rugged, stackable aluminum housing
- Single DMX-512 output on 5-pin XLR connector
- Supports up to 512 output channels
- One USB input connector providing power
- Multiple USB DMX Widgets can be connected via USB Hub
- Kensington security slot
- Storage Temperature 20-60°C / 0-140°F
- Compliance: ETL, CETL, CE

DMX SUPER WIDGET SPECIFICATIONS

- USB connection to any Hog 4 console as well as Hog 4 PC
- Rugged, stackable aluminum housing
- Four DMX 512 outputs on 5-pin XLR connectors
- Supports up to 2048 output channels
- One USB input connector
- Up to two USB DMX Widgets can be connected via USB Hub
- Kensington security slot
- External PSU included
- Storage Temperature 20-60°C / 0-140°F
- Compliance: ETL, CETL, CE

DMX SUPER DUPER WIDGET SPECIFICATIONS

- USB connection to any Hog 4 console as well as Hog 4 PC
- 19" Rackmount form factor
- Eight DMX-512 outputs on 5-pin XLR connectors
- Supports up to 4096 output channels
- Kensington security slot
- One USB input connector
- Storage Temperature 20-60°C / 0-140°F
- Compliance: ETL, CETL, CE
- Mains power: 100-250VAC, 50/60Hz, max 200W
- Mains connector: IEC320 C13
- Fuse: 1x 5x20mm 5AT fuse

MIDI/LTC WIDGET SPECIFICATIONS

- USB connection to any Hog 4 console as well as Hog 4 PC
- Rugged, stackable aluminum housing
- One USB input connector providing power
- One Linear Timecode (LTC/SMPTE) input on 3 pin XLR connector
- MIDI in/out/thru supporting MIDI messages, MIDI Show Control, and MIDI Time Code
- Multiple USB MIDI/LTC Widgets can be connected via USB Hub
- Kensington security slot
- Storage Temperature 20-60°C / 0-140°F
- Compliance: ETL, CETL, CE

WIDGETS DIMENSIONS

MODEL	HEIGHT		WIDTH		DEPTH		WEIGHT	
	in	mm	in	mm	in	mm	lb	kg
DMX Widget	1.8	45	2.5	65	4.2	106	0.8	0.3
DMX Super Widget	1.8	45	7.8	198	4.2	106	1.1	0.5
DMX Super Duper Widget	1.8	45	19.1	483	10.9	277	5.8	2.6
MIDI/LTC Widget	1.8	45	7.8	198	4.2	106	1.1	0.5