



# grandMA3 onPC 2Port Node 2k

Art.-No. 4010512



The grandMA3 onPC 2Port Node 2K enables 2 048 parameters with the grandMA3 onPC software offering 2 frame-synchronous DMX outputs. It's the perfect partner product to increase the parameter count of a grandMA3 onPC command wing up to the maximum of 4 096 parameters. The half width, 1RU housing is the perfect size for touring and fixed applications. A unique bracket accessory allows for alternative fixing methods if required.

MA Lighting offers the perfect solutions for getting started with. Simply download the grandMA3 onPC software and connect to any of the grandMA3 onPC products to unlock parameters.

The amount of DMX outputs varies with each grandMA3 onPC product but all of them unlock parameters for the full grandMA3 software functionality. There is no compromise in feature set and the range of products allow you to make the right choice for your budget or individual needs.

There are four choices for onPC solutions: the grandMA3 onPC command wing XT, featuring a built-in MA mother board, the grandMA3 onPC command wing, which offers the ultimate grandMA3 mobile solution, the grandMA3 onPC fader wing as fader extension, and the grandMA3 onPC xPort Nodes, which offer the most cost-effective DMX output solution for software-only show control.

Every grandMA3 onPC xPort Node is capable of handling MA-Net3, MA-Net2, sACN and Art-Net data and is fully RDM compliant. A 3.9" color display on the front face allows for simple configuration and provides a quick overview of the status of each Node.

All grandMA3 onPC xPort Nodes are equipped with a powerful processor and a 1 000 Mbit/s Ethernet connection to ensure the most reliable and stable Ethernet to DMX and vice versa conversion.

The grandMA3 onPC xPort Nodes are high quality solutions that can handle busy Ethernet connections without ditching DMX or RDM messages.



## Scope of delivery

1x powerCON TRUE1 connector (NAC3FX-W)

## Technical Specifications

<b>Parameters</b>	2 048 (HTP/LTP)
<b>Parameters Mode2</b>	1 024 (HTP/LTP)
<b>Operating voltage/ Supply voltage</b>	100-240V, 50/60Hz
<b>Power</b>	max. 15VA
<b>Operating Temperature</b>	0 °C up to 40 °C / 32 °F up to 104 °F
<b>Dimensions</b>	207 x 184 x 43 mm / 9 x 8 x 2 in (width x depth x height)
<b>Net weight</b>	2 kg / 5 lbs
<b>Connectors</b>	1 x powerCON TRUE1 1 x etherCON/RJ45 2 x DMX512-A Out (5pin XLR female) 1 x USB 2.0 (type A)

## Article

Art.-No.	Article
4010512	grandMA3 onPC 2Port Node 2k

## Accessories

Art.-No.	Article
130281	MA 2Port Node / 4Port Node 19" rack mounting kit - blank panel
130285	MA 2Port Node 19" rack mounting kit - XLR connectors
130283	MA 2Port Node / 4Port Node 19" rack mounting kit - 2x Nodes
130284	MA 2Port / 4Port / 8Port Node rigging plate
210650	Adapter cable set for MA 2Port Node, 2x cable DMX/XLR5 to DMX (length 0.5m), 1x cable RJ45, 1x built-in socket etherCON/RJ45 to RJ45
210627	Adapter cable set for MA 2Port / 4Port Node, 4x cable DMX/XLR5 to DMX (length 0.5m)
210628	Adapter cable set for MA 2Port / 4Port Node, 1x cable RJ45, 1x built-in socket etherCON/RJ45 to RJ45

## More product pictures

